

PublicLine

public charging solution



11 kW and 22 kW

Charges 2 cars simultaneously

Compatible with all grid networks

Robust, durable, low maintenance

Remote monitoring and settlement of charging costs

Distributes power efficiently with Load Balancing

Integrated with multiple software providers for customer flexibility



Technical features

Charging capacity per connector	11 kW, 22 kW
Charge mode	Mode 3, Z.E. Ready
Connector type	Type 2
Number of connectors	2
CE certified	Yes
Output power	3-phase, 400 V, 16 A and 32 A
Temperature range	-25°C to +60°C
Moisture (non-regulating)	Max. 95%
Authorization	RFID card
Information status	LED ring
Communication	GPS / GSM / UMTS / GPRS Modem / controller with RFID reader
Communication protocol	OCPP 1.2, 1.5 and 1.6

Physical properties

Designed according to	IEC 61851-1 (2010), EC 61851-22 (2002), Renault Z.E. Ready guidelines
Protection	IP54, IK10
Installation instructions	EN/IEC 61000-32 (2014), EN/IEC 61000-3-3 (2013), EN/IEC 61000-6-2 (2016), EN/IEC 61000-6-3 (2007) + A1 (2011) EN/IEC 60335-1 (2012) +A13 (2017), EN/IEC 60364-4-41 (2017) EN/IEC 60529-1 (1989) +A1 (1999) + A2 (2013), EN/IEC 60950-1 (2005) + A1 (2009) + A2 (2013), EN/IEC 60950-22 (2017), EN/IEC 61851-1 (2017), EN/IEC 61851-22 (2002), EN/IEC 62196-1 (2014), EN/IEC 62196-2 (2017)
Housing	Stainless steel
Dimensions (WxHxD)	350 x 1250 x 22 mm
Weight	30 kg (max.)
Mounting	On foundation
Standard colors	RAL 7024 (graphite gray)